

© Copyright Statement

All rights reserved. All material in this document is, unless otherwise stated, the property of **FPC International, Inc.** Copyright and other intellectual property laws protect these materials. Reproduction or retransmission of the materials, in whole or in part, in any manner, without the prior written consent of the copyright holder, is a violation of copyright law.

TRIAL EVALUATION OF FPC-1 FUEL PERFORMANCE CATALYST

BY

TRI-COUNTY TRANSIT

REPORT PREPARED BY AMERICAN QUALITY OIL COMPANY, INC.
CENTER HILL, FLORIDA
FEBRUARY 20, 1991

CONTENTS

INTRODUCTION.....PAGE 1
EQUIPMENT TESTED.....PAGE 1
TEST EQUIPMENT.....PAGE 1
TEST PROCEDURE.....PAGE 1
CONCLUSION.....PAGE 2
TEST RESULT SUMMARY.....PAGE 3

APPENDICES:

Carbon Balance Method Technical Approach

Table 1 Summary of exhaust gases

Table 2 Carbon balance fuel economy
calculation

Raw Data Sheet

INTRODUCTION

FPC-1 is a complex combustion catalyst, which when added to liquid hydrocarbon fuels at a ratio of 1:5000 effectively improves the combustion reaction, resulting in increased engine efficiency and reduced fuel consumption.

Field and laboratory tests alike indicate a potential to reduce fuel consumption in diesel fleets in the range of 4% to 9%. This report summarizes the results of controlled back-to-back field tests conducted with the cooperation of Tri-County Transit, Orlando, Florida with and without FPC-1 added to the fuel. The test procedures applied were the Carbon Balance Exhaust Emission Test at a given load and engine speed.

The Carbon Balance Test includes an analysis of engine exhaust with and without FPC-1 treated fuel.

EQUIPMENT TESTED

4 - 4v92 Detroit

TEST EQUIPMENT

The equipment and instruments involved in the carbon balance test program were:

Sun Electric SGA-9000 non-dispersive, infrared analyzer (NDIR) for measuring the exhaust gas constituents, HC (unburned hydrocarbons as hexane gas), CO, CO₂, and O₂.

An IMC and a Fluke high temperature thermometer and probes for measuring exhaust gas and ambient temperature.

TEST PROCEDURE

The carbon balance technique for determining changes in fuel consumption has been recognized by the U.S. Environment Protection Agency (EPA) since 1973. The method relies upon the measurement of engine exhaust emissions to determine fuel consumption rather than direct measurement (volumetric or gravimetric) of fuel consumption. The method produces a value of engine fuel consumption with FPC-1 relative to a baseline value established with the same vehicle.

Engine speed and load are duplicated from test to test, and measurements of exhaust and ambient temperature are made. Under these conditions a minimum of five readings were taken for each parameter after stabilization of the exhaust temperature. Four units were tested for both baseline and treated fuel segments. Each test unit was tested under steady-state conditions at respected rpm levels. Table 1 summarizes the test results.

Results indicate a reduction in fuel consumption for all units tested. The general trend of improved (reduced) fuel consumption is within the general parameters of reduced fuel consumption achievable by the use of FPC-1 Fuel Performance Catalyst. All regulated emissions were also reduced.

Also, a qualitative smoke reduction test was performed during the Tri-County Transit Test. This was done by attaching a 25 micron filter to the exhaust gas sampling train for both the baseline and treated fuel test segments. The filter traps unburned fuel exhausted from the engine as visible smoke or particulate. The filters used during the treated fuel segment of the test was cleaner indicating a significant reduction in smoke while using FPC-1 treated fuel.

Due to the fact the carbon mass balance test requires steady state conditions in order to record accurate data, units 724 and 736 were dropped from the test procedure. Due to compressor and fan cycles, fluctuations in the rpm levels made it impossible to collect accurate relative numbers.

CONCLUSION

The series of test conducted on a number of Mack powered equipment confirm that the addition of FPC-1 to the fuel will reduce fuel consumption.

1. The reduction in fuel consumption in the fleet average 2.1%.
2. The emission levels of unburned hydrocarbons (HC) were reduced 22.52%. Carbon Monoxide (CO) emissions were reduced 70%.
3. Also, the particulate filter trap comparison indicated FPC-1 treated fuel burns cleaner and emits less smoke.

TEST RESULT SUMMARY

COMPANY: Tri-County Transit, Orlando, Florida

DATE: September 8, 1990 through February 14, 1991

TESTED BY: American Quality Oil Co., Inc.

EQUIPMENT TESTED: 4 X 6v92 Detroit engines in transit buses

- RESULTS:
1. Fuel consumption reduced 2.1% avg.
 2. Carbon monoxide emissions reduced 70% avg.
 3. Emission levels of unburned hydro carbons reduced by 22.52% avg.
 4. Switched from burning 70% #1, 30% #2 untreated diesel to burning all #2 diesel treated with FPC-1.
 5. Net monthly savings of approximately \$10,500/month in fuel cost.
 6. A qualitative smoke reduction test proved FPC-1 treated fuel burns cleaner and emits less smoke.
 7. #2 diesel fuel generally has more BTU value (British Thermal Units), or in other words, it contains more energy than #1 diesel. However, because of it's lower cetane rating it is harder to get #2 to burn. However, with the addition of FPC-1 the #2 diesel is allowed to burn more efficiently than the #1 untreated diesel.
 8. Additionally, #2 diesel is more oily than #1 diesel, therefore, providing better lubrication to the upper cylinder areas of the engines.

FUEL/COST SAVINGS ANALYSIS

A.	1.	Monthly fuel savings:	157,000	Gallons/month
			<u>X 2.1%</u>	Savings w/FPC-1
			3,297	Gallons saved/monthly
	2.	Gross dollar savings:	3,297	Gallons saved/monthly
			<u>X .95</u>	Avg. cost/gallon #1 diesel
			3,132.15	Gross monthly savings
B.		Monthly dollars savings:	109,900	Gallons/month #1 diesel (70% of 157,000)
			<u>X .10</u>	Diesel/gallon
			\$10,990	Gross monthly savings
C.	(B)	10,990.00		
	(A)	+ 3,132.15		
		<u>14,122.15</u>	Total gross monthly savings	
		- 3,611.00	Cost of FPC-1/monthly	
		<u>10,511.15</u>	Net Monthly Savings	

APPENDICES

CARBON BALANCE METHOD TECHNICAL APPROACH:

A fleet of diesel powered transit buses owned and operated by Tri-County Transit were selected for the FPC-1 evaluation. The SGA-9000 exhaust analyzer and the thermocouple instrumentation were calibrated and a leak test on the sampling hose and connections was performed. Each engine was then brought up to stable operating temperature as indicated by the engine water temperature and exhaust temperature. No exhaust gas measurements were made until each engine had stabilized at the operating condition selected for the test.

The baseline fuel consumption test consisted of a minimum five sets of measurements of CO₂, CO, unburned hydrocarbons (measured as hexane gas), O₂, and exhaust temperature, made at approximately 90 second intervals for each engine.

After the baseline test, on September 18, 1990 the fuel storage tank, from which the fleet is exclusively fueled, was treated with FPC-1 at the recommended level of 1 oz. of catalyst to 40 gallons of diesel fuel (1:5000 volume ratio). The equipment then operated with the treated fuel until Feb. 14, 1991, when the fuel consumption test described above was repeated.

Throughout the entire fuel consumption test, an interval self-calibration of the exhaust analyzer was performed after every two sets of measurements to correct instrument drift. A new analyzer exhaust gas filter was installed before both the baseline and treated fuel test series.

From the exhaust gas concentrations measured during the test, the average molecular weight of the gases containing carbon can be calculated and the fuel consumption may be expressed as a "performance factor" which relates the fuel consumption of the treated fuel to the baseline. The calculations are based on the assumption that the fuel characteristics, engine operating conditions and test conditions are essentially the same throughout the test.

TABLE 1

SUMMARY OF EXHAUST GASES

	Baseline Fuel	Treated Fuel
CO	.01%	.003%
HC	5.55 ppm	4.3 ppm
CO ₂	1.39%	1.37%
O ₂	18.6%	18.9%

TABLE 2

CALCULATION FOR THE CARBON MASS BALANCE

BASELINE:

Equation 1 Volume Fractions

$$\begin{aligned} \text{VFCO}_2 &= 1.39/100 \\ &= .0139 \\ \text{VF}_02 &= 18.6/100 \\ &= .186 \\ \text{VFHC} &= 5.55/1,000,000 \\ &= .00000555 \\ \text{VFCO} &= .01/100 \\ &= .0001 \end{aligned}$$

Equation 2 Molecular Weight

$$\begin{aligned} \text{MWT}_1 &= (.00000555)(86) + (.0001)(28) + (.0139)(44) + (.186) \\ & \quad (32) + [(1 - .00000555 - .0001 - .0139 - .186)(28)] \\ \text{MWT}_1 &= 28.9667219 \end{aligned}$$

Equation 3 Calculated Performance Factor

$$\text{pf}_1 = \frac{2952.3 \times 28.9667219}{86(.00000555) + 13.89(.0001) + 13.89(.0139)}$$

$$\text{pf}_1 = 438,697 \text{ (rounded to the nearest meaningful place)}$$

TREATED

Equation 1 Volume Fractions

$$\begin{aligned} \text{VFCO}_2 &= 1.37/100 \\ &= .0137 \\ \text{VF}_02 &= 18.9/100 \\ &= .189 \\ \text{VFHC} &= 4.3/1,000,000 \\ &= .0000043 \\ \text{VFCO} &= .003/100 \\ &= .00003 \end{aligned}$$

Equation 2 Molecular Weight

$$\begin{aligned} \text{Mwt } 2 &= (.0000043)(86) + (.00003)(28) + (.0137)(44) + \\ & \quad (.189)(32) + [(1 - .0000043 - .00003 - .0137 - .189) \\ & \quad (28)] \end{aligned}$$

Mwt 2 = 28.9754494

Equation 3 Calculated Performance Factor

$$pf2 = \frac{2952.3 \times 28.9754494}{86(.0000043)+13.89(.00003)+13.89(.0137)}$$

pf2 = 447,689 (rounded to nearest meaningful place)

FINAL EQUATION FOR FUEL SAVINGS:

Equation 5 percent change in engine performance and fuel economy

$$\% \text{ change F.E.} = [447,689 - 438,697] / 438,697 (100) = 2.1\%$$