

## © Copyright Statement

All rights reserved. All material in this document is, unless otherwise stated, the property of **FPC International, Inc.** Copyright and other intellectual property laws protect these materials. Reproduction or retransmission of the materials, in whole or in part, in any manner, without the prior written consent of the copyright holder, is a violation of copyright law.

**Comparison of a Baseline Fuel Consumption Rate  
to Four (4) FPC-1 Treated Fuel Consumption  
Rates in a Fleet of Kenworth T6000 tractors over  
a Fourteen (14) Month Test Period**

Report Prepared BY

FPC Technology, INC.  
Boise, Idaho

And

RDI Construction, Inc.  
South Point, Ohio

September 30, 1993

## I. Introduction:

Beginning in June of 1992, RDI and FPC Technology, Inc. (FPCT), initiated a study of the effectiveness of FPC-1 Fuel Performance catalyst in a fleet of T6000 Kenworth tractors owned and operated by Ore-Ida Foods, Inc., Ontario, Oregon. The original fleet was comprised of 10, Caterpillar 3406 TA powered tractors. The test procedure was the carbon mass balance calculation adapted for field use by RDI Inc. The procedure measures the carbon mass in the exhaust while the vehicle is stationary and operating under steady-state engine conditions.

The study was originally intended to document fuel consumption reductions created by the addition of FPC-1 to standard #2D fuel after an engine conditioning period of 8,000 to 10,000 miles. Later, the study was expanded to determine the effectiveness of the catalyst after approximately 20,000 miles of treated fuel use. Finally, after approximately one year of catalyst treatment, a third study was conducted comparing fuel consumption rate with FPC-1 fuel treatment to the fuel consumption after fuel treatment with the FPC-1 formulation in a new solvent carrier.

The several studies made it possible to determine the long term effectiveness of FPC-1, the accuracy of the test method, and the effectiveness of FPC-1 in the new carrier base.

## II. Test Sequence # 1

The first test sequence was conducted using untreated #2D (PF1). Once completed, the test fleet was treated with FPC-1 at a 1:5000 mixing ratio, and put back into normal operation for approximately 90 days. The test procedure was repeated in September of 1992, this time with FPC-1 treated #2 D (PF2). Table 1 compares the baseline and treated fuel engine performance factors (PF) and percent change in fuel consumption ( $PF2-PF1/PF1 \times 100$ ) after the 90 day period of FPC-1 use. Seven of the original ten units were available for testing with treated fuel.

**Table 1. Fuel Consumption Reduction PF2-FP1PF1**

<u>Unit No.</u>	<u>PF1(Base)</u>	<u>PF2 (FPC-1)</u>
30	354,022	*399,491
28	365,054	389,190
25	358,950	375,600
37	375,389	420,347
41	378,003	384,917
40	355,245	397,044
42	393.891	401,804
Average:	368,651	395,484
% Change:	<b>7.28%</b>	

**A positive change in PF equates to a reduction in fuel consumption.**

### III. Test Sequence #2

Laboratory data indicates a definite engine preconditioning period before maximum fuel consumption reduction can be realized after FPC-1 fuel treatment. The test fleet had accumulated only 8,000 miles of FPC-1 use during the 90 day test period. Engineers wanted to determine if an additional 8,000 to 10,000 miles would effect a greater reduction in fuel consumption. Accordingly, since the test fleet was using FPC-1 on a regular basis, a second carbon mass balance was conducted after the fleet had accumulated an additional 10,000 miles. Table 2 compares the baseline to the second treated fuel (PF3) and presents the fuel consumption reduction. Three of the units tested during the baseline were available for the second treated fuel test segment.

**Table 2. Fuel Consumption Reduction PF3-PF1/PF1**

<u>Unit No.</u>	<u>PF (Base)</u>	<u>PF3 (FPC-1)</u>
25	358,950	*396,212
37	407,908	407,908
41	378,003	387,414
Average:	370,780	397,311
% Change:	<b>7.16%</b>	

- A positive change in PF equates to a reduction in fuel consumption.

The study appeared to demonstrate maximum FPC-1 benefit can be obtained in an 8,000 mile road test. Further, the study confirmed the accuracy of the data and results obtained from the first test sequence. Note the engine performance factors (PF1,PF2, and PF3) show good repeatability.

### IV. Test Sequence #3

During the summer of 1993, RDI as part of its continuous program to develop and improve FPC-1, produced a high flash point solvent carrier for FPC-1. Due to the consistency of the data collected in the previous tests of the Kenworth fleet, this fleet was selected for a trial evaluation of FPC-1 and the new carrier.

Although the purpose of this test was to establish a new baseline with FPC-1 treated fuel and compare any change from the baseline after the addition of FPC-1 in the new carrier, the study allowed for an additional comparison of the effectiveness of FPC-1, and the accuracy of the carbon mass balance field adaptation.

The FPC-1 baseline was conducted in August of 1993 (PF4). Table 4 makes the comparison of the August '93 FPC-1 baseline to the June '92 untreated baseline (PF1). Four of the trucks baselined on untreated fuel were available for comparison.

**Table 3. Fuel Consumption Reduction PF4-PF1/PF1**

<u>Unit No.</u>	<u>PF1 (Base)</u>	<u>PF4 (FPC-1)</u>
37	375,389	*420,902
41	378,003	401,001
40	355,245	418,195
42	393,891	414,174
Average:	375,632	413,568
% Change:	<b>10.10%</b>	

- A positive change in PF equates to a reduction in fuel consumption.

The data indicate greater improvement in fuel consumption after long term FPC-1 use. An examination of truck maintenance showed none of the trucks in the test sample had undergone major repairs.

V. Test Sequence #4

The 4<sup>th</sup> and final test sequence was conducted after 8,000 miles of FPC-1 and the new carrier. Although designed to compare FPC-1 baseline fuel consumption to FPC-1 new carrier fuel consumption, the data can be used to determine the continued effectiveness and the accuracy of the carbon mass balance. Table 4 compares the FPC-1 new carrier data (PF5) to the original baseline (PF1).

**Table 4. Fuel Consumption Reduction PF5- PF1/PF1**

<u>Unit No.</u>	<u>PF1 (Base)</u>	<u>**PF5 (FPC-1)</u>
37	375,389	*418,451
41	378,003	391,059
40	355,245	417,964
Average:	369,546	409,159
% Change:	<b>10.72%</b>	

\*A positive change in PF equates to a reduction in fuel consumption.

\*\* New Carrier

VI. Appendices

A description of the carbon mass balance technical approach is attached as Appendix 1. A bar graph of the results is attached as Appendix 2.

## VII. Conclusion

The following conclusions can be made from an analysis of the data from the several test sequences shown above.

- 1) FPC-1 new carrier is at least as effective as baseline FPC-1
- 2) Fuel consumption reductions may not be maximized in the CAT 3406 engine in a short term test
- 3) Fuel consumption reductions averaged approximately 10% in the Cat 3406 engines after nearly 14 months of FPC-1 fuel treatment.
- 4) The carbon mass balance procedure adapted for field use by RDI is an accurate method of determining changes in fuel consumption. The data indicate the method is accurate to less than 1 %.

# **APPENDICES**

## **CARBON BALANCE METHOD TECHNICAL APPROACH**

A fleet of Cat 3406 TA powered trucks owned and operated by Ore-Ida Foods, Inc. of Ontario, Oregon, was selected for a FPC-1 field test to determine the effect of FPC-1 on engine performance.

All test instruments were calibrated prior to both baseline and treated fuel data collection. The SGA-9000 was calibrated using Scott Calibration Gases (I/M Protocol Gases), a leak test on the sampling hose and connection was performed.

Each engine was then brought up to stable operating temperature as indicated by the engine water, oil, and exhaust temperature. No exhaust gas measurements were made until each engine had stabilized at the rpm selected for the test. #2 Diesel fuel was exclusively used throughout the evaluation. Fuel specific gravity and temperature were taken before testing.

The baseline fuel consumption test consisted of a minimum of five sets of measurements of CO<sub>2</sub>, CO, HC, O<sub>2</sub> and exhaust temperature and pressure made at 90 second intervals. Each engine was tested in the same manner.

After the baseline test, the fuel storage tank, from which the fleet is exclusively fueled, was treated with FPC-1 at the recommended level of 1 oz. catalyst to 40 gallons of diesel fuel (1:5000 volume ratio). The equipment was then put back into operation with the treated fuel until the trucks were retested. At this time, the test described above was repeated for each engine, only this time with FPC-1 treated fuel.

Throughout the entire fuel consumption test, an internal self-calibration of the exhaust analyzer was performed after every two sets of measurements to correct instrument drift, if any. A new analyzer exhaust gas filter was installed before both the baseline and treated fuel test series.

From the exhaust gas concentrations measured during the test, the molecular weight of each constituent, and the temperature and mass flow rate of the exhaust stream, the fuel consumption may be expressed as a “performance factor” which relates the fuel consumption of the treated fuel to the baseline. The calculations are based on the assumption that engine operating conditions are essentially the same throughout the test.

Engines with known mechanical problems or having undergone repairs affecting the fuel consumption are removed from the sample.